ARCHITECTS SPECIFICATIONS MODEL 8208EMC LED BASKETBALL SCOREBOARD

INDOOR SCOREBOARD

8208EMC

BASKETBALL Volleyball **Segment Timer**



| OVERALL DIMENSION | 3'10" high x 8' wide x 5" deep. |
|-----------------------|---|
| INFORMATION DISPLAYED | Game Time, Home and Guest Score, Period, Time Outs Left, Fouls, Double Bonus, Possession. |
| DIGITS | Bright Red and Amber, 7-Segment LEDs. |
| GAME TIME | 12" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable. May display Time Of Day when not in use and during select sports. |
| SCORE | 10" High Amber Digits, Shall register 0-199. |
| PERIOD | 8" High Red Digits, Shall register 1-4 (may display up to 9). |
| TIME OUTS LEFT | 8" High Red Digits, Shall register 1-3 (may display up to 9). |
| POSSESSION | Indicated by 2" Red LED Indicators. |
| BONUS / DOUBLE BONUS | Indicated by 2" Amber LED Indicators. |
| CAPTIONS | White vinyl letters. |
| EMC | Built in Everbrite Message Center: a text only message center with 6" character height (8x112 Pixel Matrix). Send 99 different looped programs and 99 different messages instantly during gameplay. Second console required for instant messages. |
| CONSTRUCTION | 5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green, custom colors available). |
| ELECTRONICS | 100% solid state, microprocessor controlled system. |
| HORN | Includes external 100 dB horn. 120 dB trumpet horn is available. |
| SERVICING | Front access for ease of servicing. Plug in modules for ease of replacement. |
| CONSOLE | Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control available. |
| JUNCTION BOX | One junction box 5" x 3" with cover and plug. (Hardwire) |
| DATA CABLE | Twisted pair, direct burial, RJ45 Connectors. |
| POWER REQUIREMENTS | 120VAC. Minimum one 20A circuit is recommended. |
| INSTALLATION | May be mounted to nearly any wall surface. |
| WEIGHT | Net 124 lbs / Shipping 185 lbs. |
| WARRANTY | Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label. |