

ARCHITECTS SPECIFICATIONS MODEL 8213TN LED BASKETBALL SCOREBOARD

INDOOR SCOREBOARD	
8213TN Basketball Volleyball Segment Timer	PIRATES I IIGERS ALL-AMERICAN SCOREBOARDS IIIGERS BB FOULS FOULS FOULS FOULS DEFIOD T.O.L. PERIOD
OVERALL DIMENSION	3'7"high x 13' wide x 5" deep.
INFORMATION DISPLAYED	Game Time, Home and Guest Score, Period, Time Outs Left, Team Fouls, Double Bonus,
DIGITS	Possession. May display Time Of Day when not in use and during select sports. Bright White and Red, 7-Segment LEDs (Amber and Green Digits and Indicators Available).
GAME TIME SCORE	14" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable.
PERIOD	12" High White Digits, Shall register 0-199. 10" High White Digit, Shall register 1-4.
TIME OUTS LEFT	10" High White Digits, Shall Register 1-4.
FOULS	10" High White Digits, Shall Register 1-19.
POSSESSION	Indicated by 6" High White LED Arrow Indicators.
BONUS / DOUBLE BONUS	Indicated by 2"White LED Indicators.
ELECTRONIC TEAM NAMES	5.5" Team Names, 8x40 Matrix. 6-10 Characters. Also Available in Red or Amber LEDs.
CAPTIONS	White vinyl letters.
	-
CONSTRUCTION	5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate. Standard Colors: Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green. Custom colors available.
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL	Extruded Aluminum, high impact low profile microprocessor control console, latest state
CONSOLE	of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor
	to be supplied with 25 feet of cable (hardwire). Microprocessor control console with
	membrane keyboard provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Twisted pair, direct burial, RJ45 Connectors.
POWER REQUIREMENTS	120VAC. Minimum one 20A circuit is recommended.
INSTALLATION	May be mounted to nearly any wall surface.
WEIGHT	Net 180 lbs / Shipping 280 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service
	for parts in warranty. Union label.

