

**INDOOR SCOREBOARD**

**8214-4**

**4-Sided Scoreboard**  
**Basketball**  
**Volleyball**  
**Wrestling**



**OVERALL DIMENSION**

5' high x 9' wide (Each Scoreboard).  
Ad panels and Everbrite Message Centers available.

**INFORMATION DISPLAYED**

Game Time, Home and Guest Score, Period, Time Outs Left, Fouls, Double Bonus, Possession.

**DIGITS**

Bright Red and Amber, 7-Segment LEDs.

**GAME TIME**

14" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable.

**SCORE**

12" High Amber Digits, Shall register 0-199.

**PERIOD**

10" High Red Digit, Shall register 1-4, 0 (overtime). May display up to 9.

**TIME OUTS LEFT**

10" High Amber Digits, Shall register 0-9.

**POSSESSION**

Indicated by 2" Red LED Indicators.

**BONUS / DOUBLE BONUS**

Indicated by 2" Amber LED Indicators.

**TEAM FOULS**

10" High Amber Digits, Shall register 0-19. Programmable to stop at 10.

**PLAYER FOULS**

10" High Red Digits, Shall register 00-99 & 0-9.

**CAPTIONS**

White vinyl letters.

**CONSTRUCTION**

5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Dark Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green, custom colors available).

**ELECTRONICS**

100% solid state, microprocessor controlled system.

**SERVICING**

Faces slide out for servicing. Plug in modules for ease of replacement.

**MICROPROCESSOR  
CONTROL CONSOLE**

Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available. Scoreboards can be run independently or as a single 4-Sided unit. Independant operation requires multiple radios or hard-wire connections.

**JUNCTION BOX**

One junction box 5" x 3" with cover and plug. (Hardwire)

**DATA CABLE**

Twisted pair, direct burial, RJ45 Connectors. (Hardwire)

**POWER REQUIREMENTS**

120VAC. Minimum one 20A circuit is recommended.

**INSTALLATION**

May be installed permanently by four (4) cables or suspended by electric hoist (not supplied).

**WEIGHT**

Net 750 lbs / Shipping 950 lbs. (+Ad Panels, and Message Centers)

**WARRANTY**

Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.