

ARCHITECTS SPECIFICATIONS

MODEL 8214TN LED BASKETBALL SCOREBOARD SCOREBOARDS INDOOR SCOREBOARD DENTIRA 8214TN **Basketball** T.O.L Volleyball Wrestling **Segment Timer BONUS** BONUS PERIOD **FOULS PLAYER FOUL FOULS** Andrew SCORE SCORE MATCH **OVERALL DIMENSION** 5'high x 9' wide x 5" deep. INFORMATION DISPLAYED Game Time, Home and Guest Score, Period, Time Outs Left, Fouls, Double Bonus, Possession. May display Time Of Day when not in use and during select sports. Bright Red and Amber, 7-Segment LEDs. **DIGITS** 14" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable. **GAME TIME SCORE** 12" High Amber Digits, Shall register 0-199. **PERIOD** 10" High Red Digit, Shall register 1-4. TIME OUTS LEFT 10" High Amber Digits, Shall Register 1-9. **FOULS** 10" High Red Digits, Shall Register 1-19. **PLAYER** 10" High Amber Digits, Shall Register 00-99. **PLAYER FOUL** 10" High Amber Digits, Shall register 0-9. Indicated by 2" Red LED Indicators. **POSSESSION BONUS / DOUBLE BONUS** Indicated by 2" Amber LED Indicators. **ELECTRONIC TEAM NAMES** 5.5" Team Names, 8x40 Matrix. Average of 7 Characters. Available in Red or Amber LEDs. **CAPTIONS** White vinyl letters. CONSTRUCTION 5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green, custom colors available). **ELECTRONICS** 100% solid state, microprocessor controlled system. SERVICING Front access for ease of servicing. Plug in modules for ease of replacement. MICROPROCESSOR CONTROL Extruded Aluminum, high impact low profile microprocessor control console, latest state **CONSOLE** to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.



POWER REQUIREMENTS

of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor

One junction box 5" x 3" with cover and plug. (Hardwire) Twisted pair, direct burial, RJ45 Connectors.

120VAC. Minimum one 20A circuit is recommended.

INSTALLATION May be mounted to nearly any wall surface.

WEIGHT Net 156 lbs / Shipping 264 lbs.

Five year guarantee against defects in materials and workmanship. Factory repair service WARRANTY for parts in warranty. Union label.