

## ARCHITECTS SPECIFICATIONS MODEL 8218TN LED BASKETBALL SCOREBOARD

## INDOOR SCOREBOARD 8218TN **Basketball** T.O.L. Volleyball Wrestling BONUS BONUS ••• PERIOD **Segment Timer FOULS PLAYER FOUL FOULS** SCORE MATCH SCORE 6'10"high x 12' wide x 5" deep. **OVERALL DIMENSION** INFORMATION DISPLAYED Game Time, Home and Guest Score, Period, Time Outs Left, Fouls, Double Bonus, Possession. May also be used for wrestling. Bright Red and Amber, 7-Segment LEDs. **DIGITS GAME TIME** 18" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable. **SCORE** 16" High Amber Digits, Shall register 0-199. PERIOD 14" High Red Digits, Shall register 1-4, 0 (overtime). **TIME OUTS LEFT** 14" High Amber Digits, Shall register 0-9. 14" High Red Digits, Shall Register 1-19. **FOULS PLAYER** 14" High Amber Digits, Shall Register 00-99. **PLAYER FOUL** 14" High Amber Digits, Shall register 0-9. **POSSESSION** Indicated by 2" Red LED Indicators. Indicated by 2" Amber LED Indicators. **BONUS / DOUBLE BONUS** 5.5" Team Names, 8x48 Matrix. Average of 9 Characters. Available in Red or Amber LEDs. **LED ELECTRONIC TEAM NAMES CAPTIONS** White vinyl letters. CONSTRUCTION 5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green, custom colors available). **ELECTRONICS** 100% solid state, microprocessor controlled system. **HORN** Includes external 100 dB horn. 120dB Trumpet horn is available. **SERVICING** Front access for ease of servicing. Plug in modules for ease of replacement. MICROPROCESSOR CONTROL Extruded Aluminum, high impact low profile microprocessor control console, latest state **CONSOLE** of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available. **JUNCTION BOX** One junction box 5" x 3" with cover and plug. (Hardwire) **DATA CABLE** Twisted pair, direct burial, RJ45 Connectors. **POWER REQUIREMENTS** 120VAC. Minimum one 20A circuit is recommended. **INSTALLATION** May be mounted to nearly any wall surface. WEIGHT Net 251 lbs / Shipping 375 lbs. **WARRANTY** Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.

