

OUTDOOR SCOREBOARD
8493
3 DIGIT TIMER

OVERALL DIMENSION

3" high x 4'8" wide x 4.75" deep.

INFORMATION DISPLAYED

3 Digit Timer.

DIGITS

7-Segment, Bright Red LEDs.

TIMER

Three (3) 24" High Digits.

CONSTRUCTION

5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green, custom colors available).

ELECTRONICS

100% solid state, microprocessor controlled system.

SERVICING

Front access for ease of servicing. Plug in modules for ease of replacement.

**MICROPROCESSOR CONTROL
 CONSOLE**


Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available*.

*8000 Series Radio Console is available, however the ID numbers will not be displayed on the scoreboard. Recommend a hardwire console with a radio remote.

JUNCTION BOX

One junction box 5" x 3" with cover and plug mounted to back of scoreboard. (Hardwire)

DATA CABLE

Twisted pair, direct burial, RJ45 Connectors.

POWER REQUIREMENTS

115 VAC, 60 Hz. Minimum one 20A circuit is recommended. (each)

INSTALLATION

May be installed on two posts. Mounting brackets are supplied with scoreboard. Wall mount also available. May also be mounted to the DOG Timer Cart, PN 152262.

WEIGHT

Net 60 lbs. / Shipping 110 lbs. (each)

WARRANTY

Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.