

**INDOOR SCOREBOARD**  
**8514-4**  
**4-Sided Hockey Scoreboard**



Face panels may be switched upon ordering - scores on bottom and penalties on top.

<b>OVERALL DIMENSION</b>	5'high x 9' wide x 5" deep (scoreboard). Corner ad panels can vary in size depending on artwork.
<b>INFORMATION DISPLAYED</b>	Game Time, Home and Guest Score, Goal, Period, Player Number and Penalty (Score and time can be shown at bottom of scoreboard. Request must be made during order.)
<b>DIGITS</b>	Bright Red and Amber, 7-Segment LEDs.
<b>GAME TIME</b>	14" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable.
<b>SCORE</b>	12" High Amber Digits, Shall register 0-99.
<b>PERIOD</b>	10" High Red Digit, Shall register 1-3, 0 (may be edited to 9).
<b>PLAYER NUMBER</b>	10" High Amber Digits, Shall Register 00-99.
<b>PENALTY TIME</b>	10" High Red Digits, Shall Register 0:00-9:59.
<b>GOAL INDICATORS</b>	Indicated by 2" Red LED Indicators.
<b>CAPTIONS</b>	White vinyl letters.
<b>CONSTRUCTION</b>	5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Dark Blue, Bright Blue, Violet, Maroon, Red, Dark Green, Green, custom colors available).
<b>ELECTRONICS</b>	100% solid state, microprocessor controlled system.
<b>SERVICING</b>	Front access for ease of servicing. Plug in modules for ease of replacement.
<b>MICROPROCESSOR CONTROL CONSOLE</b>	Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available. Each scoreboard may be controlled seperately (optional) or controlled as one unit.
<b>JUNCTION BOX</b>	One junction box 5" x 3" with cover and plug. (Hardwire)
<b>DATA CABLE</b>	Twisted pair, direct burial, RJ45 Connectors. (Hardwire)
<b>POWER REQUIREMENTS</b>	120VAC. Minimum one 30A circuit or four 15A circuit is recommended.
<b>INSTALLATION</b>	May be installed permanently by four (4) cables or suspended by electric hoist (not supplied).
<b>WEIGHT</b>	Net 750-1000 lbs / Shipping 1000-1250 lbs (depending of ad panels).
<b>WARRANTY</b>	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.