


SCOREBOARDS™
OUTDOOR SCOREBOARD
8782TN SOCCER



OVERALL DIMENSION	8' high x 20' wide x 4.75" deep.
INFORMATION DISPLAYED	Game Time, Home Score, Guest Score, Shots on Goal, Corner Kicks, Half
DIGITS	Bright Red, 7-Segment LEDs
TIMER	24" High Digits, Shall register 0:00 - 99:59
SCORING	21" High Digits, Shall register 0-99.
SHOTS ON GOAL	21" High Digits, Shall register 0-99.
CORNER KICKS	21" High Digits, Shall register 0-99.
HALF	4" Bullseye Indicators.
ELECTRONIC TEAM NAMES	9" LED cations, 8x48 Matrix (4 LEDs per Pixel). Displays 8-12 characters.
CAPTIONS	White vinyl captions.
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal, finished in choice of colors (Black, Navy, Blue, Light Blue, Purple, Burgundy, Red, Forest Green, Green, custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL CONSOLE	Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Twisted pair, direct burial, RJ45 connectors.
POWER REQUIREMENTS	115 VAC. One 20A circuit is recommended.
INSTALLATION	May be installed on two posts. Mounting brackets are supplied with scoreboard.
WEIGHT	Net 563 lbs. / Shipping 700 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.

