

ARCHITECTS SPECIFICATIONS MODEL 8909 LED WHIRLYBALL SCOREBOARD

INDOOR SCOREBOARD

8909 Whirlyball

RED		•4 (YELLOW
PERIOD 1	KEY	POSS	PERIOD 2

OVERALL DIMENSION	3' high x 9' wide x 5" deep.		
INFORMATION DISPLAYED	Game Time, Red and Yellow Score, Key, Poss, Period		
DIGITS	Bright Red and Amber, 7-Segment LEDs.		
GAME TIME	14" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable.		
SCORE	12" High Amber Digits, Shall register 0-199.		
PERIOD	Indicated by 2" Red LED Indicators.		
КЕҮ	10" High Amber Digits, Shall register 1-5, customizable.		
POSSESSION	10" High Amber Digits, Shall register 0-30, customizable.		
CAPTIONS	White vinyl letters.		
CONSTRUCTION	5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Dark Blue, Bright Blue, Violet, Maroon, Red, Dark Green, Green, custom colors available).		
ELECTRONICS	100% solid state, microprocessor controlled system.		
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.		
MICROPROCESSOR CONTROL CONSOLE	Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.		
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)		
DATA CABLE	Twisted pair, direct burial, RJ45 Connectors.		
POWER REQUIREMENTS	120VAC. Minimum one 20A circuit is recommended.		
INSTALLATION	May be mounted to nearly any wall surface.		
WEIGHT	Net 101 lbs / Shipping 190 lbs.		
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.		

www.allamericanscoreboards.com | Specifications subject to change without notice.