

Locker Room Monitor / Timer	ALEXENSE TRANSPORTED TO THE PROPERTY OF THE PR
OVERALL DIMENSION	1' high x 2' wide x 4.75" deep.
INFORMATION DISPLAYED	Game Time / Intermission Time / Segment Time / Time of Day.
DIGITS	Bright Red, 7-Segment LEDs.
SHOT CLOCK TIME	5" High Red Digits, Shall register 00:00 - 59:59
CONSTRUCTION	4.75" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Dark Blue, Bright Blue, Violet, Maroon, Red, Dark Green, Green, custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL CONSOLE	May be hardwired in to existing scoreboard (no console required). As a stand-alone unit, console is made of extruded aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6.6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. Data can also be sent directly to timer via RJ45 connection.
DATA CABLE	Twisted pair, direct burial, RJ45 Connectors.
POWER REQUIREMENTS	120VAC. One 15A circuit is recommended.
INSTALLATION	May be mounted to nearly any wall surface.
WEIGHT	Net 10 lbs / Shipping 20 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.

www.allamericanscoreboards.com | Specifications subject to change without notice.