

OUTDOOR SCOREBOARD

8336LSTN

Line Score Baseball

AT BAT	4	BALL	1	STRIKE	2	OUT	2		2:13				
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	1	0	2	0	0	0				3	6	0
HOME	0	0	2	3	0	0					5	10	1

OVERALL DIMENSION

9' high x 36' wide x 4.75" deep.

INFORMATION DISPLAYED

Home Line Score, Guest Line Score, Ball, Strike, Out, Runs, Hits, Errors, At Bat, Time, On Base Indicators

DIGITS

Bright Red, 7-Segment LEDs. Amber, Green and White LEDs available,

SCORING

18" High Digits, Inning shall register 0-9. Runs shall register 0-99.

HITS

18" High Digits, Shall register 0-99.

ERRORS

18" High Digits, Shall register 0-9.

BALL

24" High Digits, Shall Register 1-3.

STRIKE

24" High Digits, Shall Register 1-2.

OUT

24" High Digits, Shall Register 1-2.

AT BAT

24" High Digits, Shall register 0-99.

Game Time / Time of Day

24" High Digits, Shall register 00-99, H, E, E1-E9

RUNNERS ON BASE

4" LED Bulls Eye, Displays runners on first, second and/or third base.

ELECTRONIC TEAM NAMES

11.5" LED cations, 16x80 Matrix. Displays 7-10 characters. Programmable directly from the 8000 MultiSport Console.

CAPTIONS

White vinyl letters.

CONSTRUCTION

4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal, finished in choice of colors (Black, Navy, Blue, Bright Blue, Purple, Burgundy, Red, Forest Green, Green, custom colors available).

ELECTRONICS

100% solid state, microprocessor controlled system.

SERVICING

Front access for ease of servicing. Plug in modules for ease of replacement.

MICROPROCESSOR CONTROL CONSOLE



Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.

JUNCTION BOX

One junction box 5" x 3" with cover and plug. (Hardwire)

DATA CABLE

Twisted pair, direct burial, RJ45.

POWER REQUIREMENTS

12Amps (max) at 115 VAC, 60 Hz. Minimum one 20A circuit is recommended.

INSTALLATION

May be installed on four posts. Mounting brackets are supplied with scoreboard.

WEIGHT

Net 1327 lbs. / Shipping 1653 lbs.

WARRANTY

Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.