S C O R E B O A R D S OUTDOOR SCOREBOARD 8357PC Baseball	Image: Construction of the system of the
OVERALL DIMENSION	5' high x 6' wide x 4.75" deep.
INFORMATION DISPLAYED	Home Score, Guest Score, Inning, Ball, Strike, Out, Pitch Count
DIGITS	7-Segment, Bright Red LEDs.
SCORING	14" High Digits, Shall register 0-99.
INNING	12" High Digits, Shall register 1-9.
BALL	4" Bulls Eye Indicators.
STRIKE	4"Bulls Eye Indicators.
OUT	4" Bulls Eye Indicators.
PITCH COUNT	10" High Digits, Shall register 0-199.
CAPTIONS	White vinyl letters.
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Dark Blue, Bright Blue, Violet, Maroon, Red, Dark Green, Green, custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL CONSOLE	Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Twisted pair, direct burial RJ45 Connectors.
POWER REQUIREMENTS	115 VAC, 60 Hz Minimum one 20A circuit is recommended.
INSTALLATION	May be installed on two posts. Mounting brackets are supplied with scoreboard.
WEIGHT	Net 140 lbs. / Shipping 190 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.

repair service for parts in warranty. Union label. www.allamericanscoreboards.com | Specifications subject to change without notice.