

## ARCHITECTS SPECIFICATIONS MODEL 8214C LED BASKETBALL SCOREBOARD

## INDOOR SCOREBOARD HOME 8214C **Basketball** Wrestling Volleyball POSS **Segment Timer** BONUS **BONUS PERIOD FOULS PLAYER FOUL FOULS** ALL AMERICAN SCORE MATCH **OVERALL DIMENSION** 5'high x 9' wide x 5" deep. Game Time, Home and Guest Score, Period, Fouls, Double Bonus, Possession. May also be INFORMATION DISPLAYED used for wrestling, Volleyball, and Segment Timimg. Bright Red and Amber, 7-Segment LEDs. **DIGITS GAME TIME** 14" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable. **SCORE** 12" High Amber Digits, Shall register 0-199. **PERIOD** 10" High Red Digit, Shall register 1-4. 10" High Red Digits, Shall Register 1-19. **FOULS PLAYER** 10" High Amber Digits, Shall Register 00-99. **PLAYER FOUL** 10" High Amber Digits, Shall register 0-9. **POSSESSION** Indicated by 2" Red LED Indicators. **BONUS / DOUBLE BONUS** Indicated by 2" Amber LED Indicators. **HORN** Includes external 100 dB horn. 120dB Trumpet horn is available. **CAPTIONS** White vinyl letters. CONSTRUCTION 5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Blue, Light Blue, Purple, Burgundy, Red, Forest Green, Green, custom colors available). **ELECTRONICS** 100% solid state, microprocessor controlled system. **SERVICING** Front access for ease of servicing. Plug in modules for ease of replacement. MICROPROC Extruded Aluminum, high impact low profile microprocessor control console, latest state ATT AMERICAN **CONSOLE** of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available. One junction box 5" x 3" with cover and plug. (Hardwire) **JUNCTION BOX DATA CABLE** Twisted pair, direct burial, RJ45 Connectors. 120VAC. Minimum one 20A circuit is recommended. **POWER REQUIREMENTS** INSTALLATION May be mounted to nearly any wall surface. WEIGHT Net 156 lbs / Shipping 264 lbs. WARRANTY Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.

