## PRODUCT SPECIFICATIONS FOOTBALL SCOREBOARD

## ALL AMERICAN SCOREBOARDS

	<figure></figure>
OVERALL DIMENSION	8' High x 20' Wide x 5" Depth. Additional 1.5" mounting flange on top and bottom. Style available in other sizes.
CONSTRUCTION	Fabricated 20 and 22 GA Powder Coated Galvanneal. 2 Cabinet design.
INFORMATION	Game Time (24" Red), Home & Guest Scores (21" Red), Down, To Go, Ball On, Quarter (21"), Possession (4" Red Indicators)
CAPTIONS	HOME, GUEST (9"), DOWN, TO GO, BALL ON, QTR (8")
HORN	Not Included. 100 dB Resonating and 110 dB external trumpet horn available, recommended to be wired at time of manufacture.
ELECTRONICS / DIGITS	100% solid state, microprocessor controlled system with locking connectors. Ultra bright, exposed Red LED digits.
SERVICING	Sign will be serviceable by removing the Home Score digit pan to access components.
COMMUNICATION	Radio communication is standard using a 2.4 GHz Frequency hopping spread spectrum transceiver. Hardwire optional on scoreboard, recommended to be installed at time of manufacture.
POWER REQUIREMENTS	120VAC, 2.6 Amp. Installer to provide connection point or junction box to scoreboard. 20 Amp circuit recommended.
INSTALLATION	May be mounted to nearly any wall surface or a minimum of 2 posts/beams. Number and size of beams is dependent on soil condition and IBC wind loading requirements. Hardware supplied to mount by drilling through the scoreboard flange and I-beam. Pressure and additional clamping system available. Pole/beam installations require supplied mounting bar on flange.
ESTIMATED WEIGHT	700 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label. UL Certified.
ADDITIONAL OPTIONS MODEL NUMBER + ( )	Time Outs Left (TOL), 5-Digit Timer (T5)*, 6-Digit Timer (T6)*. Protective Lens Kit (PLK + Model Number). White, Green, Amber digits available (Red is standard).
AVAILABLE CONTROL CONSOLE (SOLD SEPARATELY)	<ul> <li>MSC9000 (Multi-sport Desktop Console) Extruded Aluminum, high impact low profile microprocessor control console. 5" high x 10.25" wide x 9" deep.</li> <li>Weight: 4.3 lbs. Radio (1600 ft) is standard, simultaneous hardwire option included. Internal rechargeable battery. Switch between multiple sports by removing and replacing the slip sheet.</li> <li>HRFB9000 (Handheld Football Remote) 6.5" high x 3" wide x 1" deep. Radio (500 ft) is standard. Internal rechargeable battery. *Not available for track control.</li> </ul>

## PRODUCT SPECIFICATIONS **FB9224 OPTIONS**



FB9224TOL 14"Time Outs Left (TOL) digits.	HOME TOL DOWN TO GO BALL ON AL ALLER AL ALLER
FB9224T5 5-Digit (24") Timer. Track mode not available for HRFB9000. Tenths of a second will not be displayed out- side of Track Mode.	HOME GUEST
FB9224T5TOL 5-Dingit (24") Timer. 14"Time Outs Left (TOL) digits. Track mode not available for HRFB9000. Tenths of a second will not be displayed out- side of Track Mode.	HOME TOL TOL TOL TOL TOL TOL TOL TOL
FB9224T6 6-Digit (24") Timer. Track mode not available for HRFB9000. Tenths of a second will not be displayed out- side of Track Mode.	HOME • GUEST DOWN TO GO BALL ON QTR AL ANIENT
FB9224T6TOL 5-Dingit (24") Timer. 14"Time Outs Left (TOL) digits. Track mode not available for HRFB9000. Tenths of a second will not be displayed out- side of Track Mode.	HOME CLASSING CUEST TOL DOWN TO GO BALL ON AL AMENAN
PLK + MODEL NUMBER Protective Lenses installed in front of each digit assembly.	