


PRODUCT SPECIFICATIONS

LINESCORE BASEBALL SCOREBOARD



AT BAT		31		BALL		5		STRIKE		1		OUT		2				HIT/ERROR		11							
		1		2		3		4		5		6		7		8		9		10		R		H		E	
GUEST		0		3		0		0		0		0		0		2		0		0		5		9		2	
HOME		2		0		0		3		2		0		0		1		0		0		6		13		1	

STANDARD COLORS (CUSTOM COLORS AVAILABLE)	<div>BLACK</div> <div>NAVY</div> <div>BLUE</div> <div>WHITE BLUE</div> <div>SKY BLUE</div> <div>PURPLE</div> <div>BURGUNDY</div> <div>RED</div> <div>FOREST GREEN</div> <div>GREEN</div>
OVERALL DIMENSION	9' High x 36' Wide x 5" Depth. Style available in other sizes.
CONSTRUCTION	Fabricated 20 and 22 GA Powder Coated Galvanneal. 4 Cabinet Installation, (2) 4'6"x20' and (2) 4'6"x16' cabinets.
INFORMATION	Home & Guest 10 Inning Line Score (18"). Runs, Hits, Errors (18") Ball, Strike, Out (24"), At Bat, Hit/Error (24")
CAPTIONS	White vinyl captions: Home, Guest (11"). Innings, R, H, E (9"). At Bat, Ball, Strike, Out, Hit/Error (10").
HORN	Not Included. Optional 100dB or 110 dB horn available. Recommended to be wired at time of manufacture.
ELECTRONICS / DIGITS	100% solid state, microprocessor controlled system with locking connectors. Ultra bright, exposed Red LED digits.
SERVICING	Sign will be serviceable by removing the home runs face to access components.
COMMUNICATION	Radio communication is standard using a 2.4 GHz Frequency hopping spread spectrum transceiver. Hardwire optional on scoreboard, recommended to be installed at time of manufacture.
POWER REQUIREMENTS	100-270VAC, (12.5 Amp. @ 120VAC). Installer to provide connection point or junction box to scoreboard. 20 Amp circuit recommended.
INSTALLATION	May be mounted to a minimum of 4 posts/beams using the Unistrut that is mounted to the top and bottom backs of the scoreboard. Number and size of beams is dependent on soil condition and IBC wind loading requirements. Hardware supplied to pressure mount to I-Beams.
ESTIMATED WEIGHT	1400 lbs. Shipping Dimensions (2 Crates) 246"Lx25"Dx77"H, 1120 Lbs / 198"Lx25"Dx77"H, 900 lbs
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label. UL Certified.
ADDITIONAL OPTIONS MODEL NUMBER + ()	Pitch Count(PC), or Pitch Speed(PS) in place of At Bat or Hit/Error. Protective Lens Kit (PLK + Model Number). White, Green, Amber digits available (Red is standard). Deluxe Trim (different colored powdercoated top and bottom caps). LED Team Names available.
AVAILABLE CONTROL CONSOLE (SOLD SEPARATELY)	MSC9000 (Multi-sport Desktop Console) Extruded Aluminum, high impact low profile microprocessor control console. 5" high x 10.25" wide x 9" deep. Weight: 4.3 lbs. Radio (1600 ft) is standard, simultaneous hardwire option included. Internal rechargeable battery. Switch between multiple sports by removing and replacing the slip sheet.

PRODUCT SPECIFICATIONS

BA9360ABHE OPTIONS

LED TEAM NAMES

Changeable LED TEAM Names, editable from the MSC9000 Console.

AT BAT	BALL										STRIKE			OUT			HIT/ERROR		
	1	2	3	4	5	6	7	8	9	10							R	H	E
PIRATES	0	3	0	0	0	0	0	2									5	9	2
WARRIORS	2	0	0	3	2	0	0	1									6	13	1

Deluxe Trim

Different color powdercoated top and bottom caps. An upscaled, modern, permanent version of border striping.

Shown: Black Scoreboard with Orange Trim.

AT BAT	BALL										STRIKE			OUT			HIT/ERROR		
	1	2	3	4	5	6	7	8	9	10							R	H	E
GUEST	0	3	0	1	0	0											4	6	
HOME	0	1	0	2	2												5	8	

PLK + MODEL NUMBER

Protective Lenses Installed in front of each digit assembly.

